

PRODUCT DESCRIPTION

Presstite FR is an impregnated flexible polyurethane foam sealing strip. Presstite FR expands and contracts to accommodate movement, acting as a gasket or sealant to reduce noise, to stop light draughts, dust, dirt, and light rain water from entering building constructions in leisure, domestic, commercial or industrial installations.

USAGE/PURPOSE

Expansion joints precast

- Concrete slabs, block and brick work

Precast

- Concrete Panels

Roofs

- Domes, Skylights and Vents

Sheetmetal Roofing

- Profile for sealing at parapets, over plates, side and end laps

Windows and Doors Frames

- Timber, masonry and metal

FEATURES & BENEFITS

- Easy Installation
- Assessed to AS 1530.8, for a BAL40 exposure. Consult Tremco Technical Services for further information.
- Windproof

COLOUR

Black

PACKAGING

50mm x 25mm

Profile D

TYPICAL PROPERTIES		
Property	Test Method	Result
Density		95 Kg/m ³
Resilience		28%
Tensile Strength		89KPa
Elongation		90%
Tear Strength		267 N/m
Compression Set, 75%		58% at 70°C

NOTE: Typical Properties should not be used as Specifications

INSTALLATION

Presstite FR is to be applied with the foil side facing out of the roof and set back approximately 20mm from the roof or ridge cap edge.

CUTTING AND JOINING

Presstite FR can be cut with a wet knife or scissors at an angle of 45° and spliced, cut should be made at the trough of the corrugated profile.

CHECK THE SEAL

After fitting check that Presstite FR is uniformly and properly compressed with no gaps.

HEALTH & SAFETY PRECAUTIONS

The Safety Data Sheet (SDS) must be read and understood prior to use.

TECHNICAL SERVICE

Tremco has a team of Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

GUARANTEE/WARRANTY

TREMCO products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with TREMCO written instructions and (b) in any application recommended by TREMCO, but which is proved to be defective, will be replaced free of charge.

Any information provided by TREMCO in this document in relation to TREMCO's goods or their use is given in good faith and is believed by TREMCO to be appropriate and reliable. However, the information is provided as a guide only, as the actual use and application will vary with application conditions which are beyond our control. TREMCO makes no representation, guarantee or warranty relating to the accuracy or reliability of the information and assumes no obligation or liability in connection with the information. To the extent permitted by law, all warranties, expressed or implied are excluded.

