

Reference No: 8LMPE 501

## **Hazardous, Dangerous Goods**

#### 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: TREMcoat MPE Resin

Recommended use: Two component epoxy system. Use with TREMcoat MPE Hardener.

**Supplier:** Tremco CPG Australia Pty Ltd

ABN: 25 000 024 064
Street Address: 12/4 Southridge Street

Eastern Creek NSW 2766

**Telephone:** 02 9638 2755 **Facsimile:** 02 9638 2955

Emergency Telephone number: 02 9037 2994 (Aus) +1 703-741-5500 (Worldwide)

#### 2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7.





## Signal Word

Warning

### **Hazard Classifications**

Skin Irritation - Category 2 Eye Irritation - Category 2A Sensitisation - Skin - Category 1

Chronic Hazard to the Aquatic Environment - Category 2

#### **Hazard Statements**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

#### **Prevention Precautionary Statements**

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust, fume, gas, mist, vapours or spray..

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash hands, face and all exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing protective clothing, gloves, eye/face

protection and suitable respirator.

## **Response Precautionary Statements**

**Product Name: TREMcoat MPE Resin** 

P101 If medical advice is needed, have product container or label at hand.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on product label).



P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing.

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.

## **Storage Precautionary Statement**

P403 Store in a well-ventilated place.

#### **Disposal Precautionary Statement**

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

Poison Schedule: S5. Caution

## **DANGEROUS GOOD CLASSIFICATION**

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

#### Dangerous Goods Class: 9

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

(a) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or

(b) IBCs.

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

## 3. COMPOSITION INFORMATION

CHEMICAL ENTITY

CAS NO
PROPORTION

Benzyl alcohol
Bisphenol-A epoxy resin
Ingredients determined to be Non-Hazardous

CAS NO
PROPORTION

100-51-6
25068-38-6
>60 % (w/w)
Balance

\_\_\_\_

100%

#### 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic Vapour) respirator or an Airline respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**Eye contact:** If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Ingestion:** For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, DO NOT induce vomiting.

Product Name: TREMcoat MPE Resin Reference No: 8LMPE 501
Issued: 2025-02-17 Version: 2 Page 2 of 8



**PPE for First Aiders:** Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

### 5. FIRE FIGHTING MEASURES

Hazchem Code: •3Z

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible liquid.

**Fire fighting further advice:** On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

#### 6. ACCIDENTAL RELEASE MEASURES

#### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

#### **LARGE SPILLS**

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 171

## 7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is classified as a Class 9 Miscellaneous Dangerous Good as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison Schedule 5 (Caution) and must be stored, maintained and used in accordance with the relevant regulations.

Product Name: TREMcoat MPE Resin Reference No: 8LMPE 501

Issued: 2025-02-17 Version: 2 Page 3 of 8



## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Natural ventilation should be adequate under normal use conditions.

**Personal Protection Equipment:** SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Clear Liquid Odour: Not Available

Solubility in water:

Specific Gravity:

Relative Vapour Density (air=1):

Vapour Pressure:

Flash Point (°C):

Insoluble

1.1 to 1.2

Not Available

Not Available

>154°C (cc)

Explosion/Flammability Limits: upper: Class C1 Combustible

**Autoignition Temperature (°C):** Not Available Melting Point/Range (°C): Not Available **Boiling Point/Range (°C):** Not Available **Decomposition Point (°C):** Not Available pH: Not Available Viscosity: Not Available Evaporation Rate (n-Butyl acetate=1): Not Available **Partition Coefficient:** Not Available **Explosive properties:** Not Available

% Volatile by Volume: <2%

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

### 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under recommended conditions of storage.

Conditions to avoid: Avoid heat, sparks, open flames and other ignition sources.

Product Name: TREMcoat MPE Resin Reference No: 8LMPE 501



**Incompatible materials:** Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.

**Hazardous decomposition products:** May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.

Hazardous reactions: Hazardous polymerization is not expected to occur.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

#### **Acute toxicity**

**Inhalation:** This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients):  $LC_{50} > 20.0 \text{ mg/L}$  for vapours or  $LC_{50} > 5.0 \text{ mg/L}$  for dust and mist.

**Skin contact:** This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000 \text{ mg/Kg}$  bw

**Ingestion:** This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients):  $LD_{50} > 2,000 \text{ mg/Kg bw}$ 

**Corrosion/Irritancy:** Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

**Sensitisation:** Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

**Aspiration hazard:** This material has been classified as not an aspiration hazard.

**Specific target organ toxicity (single exposure):** This material has been classified as not a specific hazard to target organs by a single exposure.

#### **Chronic Toxicity**

Mutagenicity: This material has been classified as not a mutagen.

Carcinogenicity: This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.

**Specific target organ toxicity (repeat exposure):** This material has been classified as not a specific hazard to target organs by repeat exposure.

Product Name: TREMcoat MPE Resin Reference No: 8LMPE 501

Issued: 2025-02-17 Version: 2 Page 5 of 8



### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

**Long-term aquatic hazard:** This material has been classified as a Category Chronic 2 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 1 - 10 mg/L, where the substance is not rapidly degradable and/or BCF  $\geq 500 \text{ and/or log K}_{ow} \geq 4$ .

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

#### 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

### 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Australian Special Provisions; AU01: Environmentally Hazardous Substances meeting the description of UN 3077 or UN 3082 are not subject to this Code (ADG 07) when transported by road or rail in;

- (c) packagings that do not incorporate a receptacle exceeding 500 Kg (L); or
- (d) IBCs.



UN No: 3082

Dangerous Goods Class: 9

Packing Group: III

Hazchem Code: •3Z

Emergency Response Guide No: 171

Limited Quantities 5 L

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1). Note 1: Materials that are fire risks are incompatible with oxidising agents (Class 5.1) or organic peroxides (Class 5.2). Exemptions may apply.

Product Name: TREMcoat MPE Resin Reference No: 8LMPE 501

Issued: 2025-02-17 Version: 2 Page 6 of 8



#### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 3082
Dangerous Goods Class: 9
Packing Group: III
Limited Quantities: 5 L

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

#### **AIR TRANSPORT**

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 3082

Dangerous Goods Class: 9

Packing Group: III

Limited Quantities: 30 kg G

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

## 15. REGULATORY INFORMATION

#### This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

#### This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): S5. Caution.

#### 16. OTHER INFORMATION

#### Reason for issue:

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for

Product Name: TREMcoat MPE Resin Reference No: 8LMPE 501

Issued: 2025-02-17 Version: 2 Page 7 of 8



any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: TREMcoat MPE Resin Reference No: 8LMPE 501
Issued: 2025-02-17 Version: 2 Page 8 of 8